



THIS IS GREENFIBER® STABILIZED FOR ATTICS ONLY
CELLULOSE INSULATION

Application Coverage Chart		30 lbs (13.6 kg)		INS500	
R-Value at 75° F Mean Temp. Valor de resistencia térmica (valor R) a 75 F de temperatura media	Minimum Thickness (inches) Espesor mínimo (en pulgadas)		Net Coverage (no adjustment for framing) Recubrimiento neto (Sin compensación para el entramado)		
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Cantidad máxima de pies cuadrados por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. (lbs/ft²) Peso mínimo por pie cuadrado (lb/pie2)
11	3.30	3.07	105.2	9.5	0.285
13	3.92	3.64	87.2	11.5	0.344
19	5.74	5.34	56.7	17.6	0.529
22	6.64	6.18	47.9	20.9	0.626
28	8.42	7.83	36.2	27.6	0.828
30	9.00	8.37	33.4	29.9	0.898
32	9.58	8.91	30.9	32.3	0.969
38	11.32	10.53	25.2	39.7	1.19
40	11.89	11.06	23.7	42.2	1.27
44	13.03	12.12	21.1	47.4	1.42
48	14.17	13.17	18.9	52.8	1.58
49	14.45	13.44	18.5	54.2	1.63
50	14.73	13.70	18.0	55.6	1.67
60	17.53	16.30	14.3	70.0	2.10

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 30 LBS. USING A VOLUMATIC III, 3RD GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1,000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THE INSTALLED MOISTURE CONTENT MUST BE BETWEEN 16% AND 25% IN ATTIC APPLICATIONS. THIS COVERAGE CHART DOES NOT APPLY TO DRY LOOSE-FILL ATTIC/ FLOOR APPLICATIONS. THIS PRODUCT IS NOT INTENDED FOR SPRAY APPLIED OR DRY DENSE-PACK WALL APPLICATIONS. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. MINIMUM NET WEIGHT IS 28.5 LBS.

READ THIS BEFORE YOU BUY
What you should know about R-values

This chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of the insulation you need depends on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel. To get the marked R-value, it is essential that this insulation be installed properly.

FOR MORE INFORMATION CONTACT GREENFIBER:
800.228.0024 greenfiber.info@greenfiber.com

Corporate Office:
2500 Distribution Street, Suite 200, Charlotte NC 28203
(p) 800.228.0024 (f) 704.379.0685
www.greenfiber.com

Manufacturing Locations:
Albany, NY Phoenix, AZ
Charlotte, NC Salt Lake City, UT
Delphos, OH Tampa, FL
Norfolk, NE Waco, TX

